



STANDARD

OUTSIDE


SCREENS

NOVA 520

1%

A - front

B - back




N520-1-03 light grey
width (mm) - 3000

Composition	75%PVC / 25% PES
Tensile strength (warp)	210 daN
Tearing strength (warp)	> 7 daN
Tensile strength (weft)	165 daN
Tearing strength (weft)	> 5 daN
Width (+/- 50 mm)	3000
Roll	20 m
Weight (+/- 5 cm)	520 g/m ²
Thickness	0,60 mm
Fire resistance	M1, B1

quality fabrics

A - front


B - back




N-520-3-01 white
width (mm) - 3000

A - front

B - back




N520-3-04 mouse grey
width (mm) - 3000



N520-3-02 beige
width (mm) - 3000




N520-3-06 dark grey
width (mm) - 3000



N520-3-13 pearl grey
width (mm) - 3000



N520-3-05 charcoal
width (mm) - 3000



N520-3-03 light grey
width (mm) - 3000

NOVA 520
30%

Composition	75%PVC / 25% PES
Tensile strength (warp)	210 daN
Tearing strength (warp)	> 8 daN
Tensile strength (weft)	180 daN
Tearing strength (weft)	> 8 daN
Width (+/- 50 mm)	3000
Roll	20 m
Weight (+/- 5 cm)	540 g/m ²
Thickness	0,70 mm
Fire resistance	M1, B1

quality fabrics




HEMA[®]
ZIP

10% SARGE


Composition	41,5% FG / 58,5% PVC
Tensile strength (warp)	290 daN
Tearing strength (warp)	9,5 daN
Tensile strength (weft)	210 daN
Tearing strength (weft)	10 daN
Width (+/- 50 mm)	2500
Roll	50 m
Weight (+/- 5 cm)	474 g/m ²
Thickness	0,60 mm
Fire resistance	M1, FR

quality fabrics



A - front





B - back





S600-1-108101 grey-white
width (mm) - 2500



S600-1-108108 grey
width (mm) - 2500




S600-1-108118 grey-black
width (mm) - 2500




S600-1-118118 black
width (mm) - 2500



A - front




B - back





S600-3-108101 grey-white
width (mm) - 2500, 3200





S600-3-108108 grey
width (mm) - 2500, 3200



S600-3-108118 grey-black
width (mm) - 2500, 3200



S600-3-118118 black
width (mm) - 2500, 3200



S600-3-117117 pearl
width (mm) - 2500

30%
SERGE

Composition	41,5% FG / 58,5% PVC
Tensile strength (warp)	310 daN
Tearing strength (warp)	10 daN
Tensile strength (weft)	230 daN
Tearing strength (weft)	13 daN
Width (+/- 50 mm)	2500, 3200*
Roll	2500 - 50 m 3200 - 33 m
Weight (+/- 5 cm)	544 g/m ²
Thickness	0,80 mm
Fire resistance	M1, FR, B1, C-s3, d0

quality fabrics

SERGE

50%

Composition	42% FG/ 58% PVC
Tensile strength (warp)	260 daN
Tearing strength (warp)	8,5 daN
Tensile strength (weft)	225 daN
Tearing strength (weft)	7,5 daN
Width (+/- 50 mm)	2500
Roll	50 m
Weight (+/- 5 cm)	525 g/m ²
Thickness	0,74 mm
Fire resistance	M1, B1


quality fabrics

A - front

B - back




S600-5-001010 grey-charcoal
width (mm) - 2500



S600-5-010010 charcoal
width (mm) - 2500



S600-5-008008 linen
width (mm) - 2500



S600-5-011011 bronze
width (mm) - 2500